



233SL Dual Beam Searchlight

IMPRESSIVE FROM ALL ANGLES

Uncompromised engineering, unmistakable elegance.

Jabco is proud to introduce a one-of-a-kind searchlight that is impressive from all angles. The 233SL Dual Beam Searchlight sports a clean, modern look with a multitude of new features never seen before in a searchlight of this size and price range.

Features and Benefits

- Many new innovative patent pending design solutions have been engineered into the 233SL allowing features such as spot to flood focus and 10 degree sweep.
- The 233SL is mounted by a quick release bayonet base. This is perfect for OEM installation & removal for storage and travel.
- Up to 4 wireless controllers can be fitted eliminating costly cable installations.
- The 233SL gives the marketplace a modern stylish searchlight with advanced features and innovative solutions to customer feedback that compliments today's modern motor yachts.



a xylem brand

233SL Dual Beam Searchlight IMPRESSIVE FROM ALL ANGLES

Rotation Range

The rotation range for this light is a continuous 360 degrees. There is no hard stop on this light.

Vertical Range

The vertical range for this light is 27 degrees in total. Nine from center line to full up and 18 from center line to full down.

Auto Sweep

With the light on in either fast or slow mode, pushing this button will continuously sweep the light 10 degrees each side of the initial target spot in slow mode. If the light was in fast mode when hitting the sweep button the light will automatically place the unit into slow mode. Simply press the auto sweep button again to finish the cycle. The light will return to its initial starting point and the directional controls will become available for use again.

Speed

The 233SL has the option to run the light in all motion axis's in FAST or SLOW mode. For fast simply hit the Hare button, and for slow hit the Tortoise Button.

Spot/Flood

The spot and flood buttons allow you to change the beam configuration from a spot to a flood, and allow you to choose any beam configuration you desire between these two extreme limits. Simply hold one of the buttons down until you reach your desired beam configuration. For full spot or flood simply hold the spot or flood button down until it comes to a hard stop.



Specifications	12V	24V
Part Number - OEM	60233-0512	60233-0524
Part Number - Retail	60233-0012	60233-0024
Voltage (Volts)	12	24
Current (Amps)	10	5
Mirror Diameter	3"	3"
Bulb Configuration (Watts)	55W halogen	55W halogen
Number of Bulbs	2	2
Candle Power	200,000	200,000
Beam Spread	Variable due to progressive spot to flood feature	Variable due to progressive spot to flood feature
Elevation Angle (Degrees)	Up: 9 Down: 18	9 18
Rotation Capabilities	360° continuous	360° continuous
Elevation Speed (Degrees/Seconds)	7.5	7.5
Rotation Speed (Degrees/Seconds)	Fast: 26 Slow: 10	26 10
Weight (Lbs)	6lbs*	6lbs*

*Weight is calculated using the light, mounting bracket, and controller



Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.

www.xylem.com

USA
Xylem, Inc.
Cape Ann Industrial Park
Gloucester, MA 01930
Tel: (978) 281-0440
Fax: (978) 283-2619

UK
Xylem, Inc.
Bingley Road, Hoddesdon
Hertfordshire EN11 0BU
Tel: +44 (0) 1992 450145
Fax: +44 (0) 1992 467132

GERMANY
Xylem, Inc.
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73-0
Fax: +49-40-53 53 73-11

JAPAN
NHK Jabsco Company Ltd.
3-21-10, Shin-Yokohama
Kohoku-Ku, Yokohama, 222-0033
Tel: +81-045-475-8906
Fax: +81-045-477-1162

ITALY
Xylem, Inc.
Via Tommaseo, 6
20059 Vimercate, Milano
Tel: +39 039 685 2323
Fax: +39 039 666 307